

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application. Please cancel claim 13. Please amend claims 1, 20, and 24 as follows:

Listing of Claims

1. (Currently Amended): A fork lift truck drive device ~~for a machine~~, the drive device comprising:

a traction drive system having a drive axle; and

a hydraulic work system having at least one electric motor and at least one pump driven by the electric motor,

wherein the drive axle has an axle housing that is substantially closed on all sides and is provided for connection with a vehicle frame, and wherein at least one of the electric motor and the pump of the hydraulic work system are located inside the axle housing.

~~wherein at least one of the electric motor and the pump of the hydraulic work system are integrated into the drive axle or are located directly on the drive axle.~~

2. (Original): The drive device as claimed in claim 1, wherein the drive axle has two traction motors.

3. (Original): The drive device as claimed in claim 2, wherein the traction motors are located on the ends of the drive axle and at least one of the electric motor and the pump are located axially between the traction motors.

4. (Original): The drive device as claimed in claim 2, wherein the traction motors are electric motors.

5. (Original): The drive device as claimed in claim 4, wherein the traction motors are electric disc rotor motors.

6. (Original): The drive device as claimed in claim 2, wherein the traction motors are hydraulic motors having secondary regulation systems.

7. (Original): The drive device as claimed in claim 6, wherein an installed delivery capacity of the pump is designed to deliver a volume of fluid required by the hydraulic work system.

8. (Previously Presented): A drive device for a machine, the drive device comprising:

a traction drive system having a drive axle; and

a hydraulic work system having at least one electric motor and at least one pump driven by the electric motor,

wherein at least one of the electric motor and the pump are integrated into the drive axle or are located directly on the drive axle,

wherein the drive axle has two traction motors,

wherein the traction motors are hydraulic motors having secondary regulation systems,

wherein an installed delivery capacity of the pump is designed to deliver a volume of fluid required by the hydraulic work system, and

wherein the traction motors are connected to the pump of the hydraulic work system, and the installed delivery capacity of the pump is in excess of a maximum amount required by the hydraulic work system.

9. (Original): The drive device as claimed in claim 2, including a reducing transmission installed downstream of each traction motor.

10. (Original): The drive device as claimed in claim 9, wherein the reducing transmissions are planetary gear trains.

11. (Original): The drive device as claimed in claim 1, wherein the drive axle has a single traction motor.

12. (Original): The drive device as claimed in claim 11, wherein the electric motor of the hydraulic work system is provided as the traction motor of the traction drive system.

13. (Canceled)

14. (Previously Presented): A drive device for a machine, the drive device comprising:

a traction drive system having a drive axle; and

a hydraulic work system having at least one electric motor and at least one pump driven by the electric motor,

wherein at least one of the electric motor and the pump are integrated into the drive axle or are located directly on the drive axle,

wherein the drive axle has an axle housing that is substantially closed on all sides and is provided for connection with a vehicle frame, and wherein at least one of the electric motor and the pump of the hydraulic work system are located inside the housing, and

wherein the axle housing has a housing middle segment and two housing end segments that are detachably fastened to the middle segment.

15. (Original): The drive device as claimed in claim 14, wherein at least one of the electric motor and the pump of the hydraulic work system are located in the housing middle segment.

16. (Original): The drive device as claimed in claim 14, wherein the drive axle has two traction motors and the traction motors are located in the housing middle segment.

17. (Original): The drive device as claimed in claim 14, including reducing transmissions located in the housing end segments.

18. (Original): The drive device as claimed in claim 14, wherein when the drive axle is installed, at least one housing end segment can be removed from the housing

middle segment without removing the drive axle from the vehicle frame, whereby an interior of the housing middle segment is accessible after removal of the housing end segment.

19. (Original): The drive device as claimed in claim 1, wherein the drive axle includes at least one traction motor, wherein at least one of the electric motor of the hydraulic work system and the traction motor of the traction drive system is an oil-cooled electric motor and is connected with an oil circuit of the hydraulic work system.

20. (Currently Amended): The drive device as claimed in claim ~~13~~1, wherein a control of at least one electric motor or traction motor is fastened to the outside of the axle housing.

21. (Original): The drive device as claimed in claim 20, wherein the control is oil-cooled.

22. (Original): The drive device as claimed in claim 1, including a valve control device installed on the pump of the hydraulic work system, which valve control device is integrated into the drive axle or is fastened to the outside of an axle housing in the vicinity of the pump.

23. (Original): The drive device as claimed in claim 1, including an oil tank connected to the hydraulic work system and integrated into the drive axle or located immediately next to the drive axle.

24. (Currently Amended): The drive device as claimed in claim 1, wherein the ~~machine is a fork lift truck~~is powered by an electric storage battery or by an electric fuel cell.